



WHS 40D
Soldering Station Set
Bestellnr.:0056828699
Standard Leadtime

WHS40D Digital Soldering Station 40W, 230V

- The new electronically controlled soldering station WHS40D operates with a temperature range of 150°C–450°C
- The precise soldering tip temperature shows on the digital read-out (pre-set and real value)
- This soldering station is suitable for delicate soldering tasks on temperature sensitive components
- LED to monitor the heater is integrated in the display
- The temperature adjusts via buttons
- Consist of power unit, soldering iron with “Longlife” tip 2,0 mm and support

Marketing Texte

Long description
Product claim

WHS40D Digital Soldering Station 40W, 230V

- The new electronically controlled soldering station WHS40D operates with a temperature range of 150°C–450°C
- The precise soldering tip temperature shows on the digital read-out (pre-set and real value)
- This soldering station is suitable for delicate soldering tasks on temperature sensitive components
- LED to monitor the heater is integrated in the display
- The temperature adjusts via buttons
- Consist of power unit, soldering iron with “Longlife” tip 2,0 mm and support

Short description

Soldering Station Set

Packaging information

Shelf pack size (Units per shelf pack) 1
Weight of Shelf pack 1.46 Kg

Technical Data

| | |
|-----------------------------|---|
| Display technology | LED |
| Content piece description | <ul style="list-style-type: none"> • Soldering iron with "Longlife" tip 2,0mm • Sponge (2 pcs.) • Spring with funnel |
| Temperatur control comment | Button |
| Display included & Size | Medium |
| Display information content | Medium |
| ESD safe | Yes |

| | |
|---|--------------|
| Equipotential Bonding/ hard grounding | No |
| Display backlight | No |
| Antistatic housing | No |
| Power unit wattage | 40 W |
| Mains supply Voltage | 230 V |
| Power supply frequency | 50 Hz |
| Output voltage | 18 V |
| Protection class Soldering iron | 3 |
| Protection class Control/ Power unit | 2 |
| Number of tools controlled simultaneously | 1 |
| Temperature regulation | 150 - 450 °C |

language:1|iso:en

